PRODUCT SPECIFICATIONS FOR 300.9D

Operating Weight - Without Sa	fety Frame	2061 lb
Digging Force - Bucket		2000 lb
Digging Force - Stick		1011 lb
Operating Weight - With Safety	Frame	2170 lb
Net Power	13 HP	
Engine Model	Yanmar 31NV70	
Rated Speed	2100 r/min	
Maximum Engine Output	18 HP	
Gross Power - ISO 14396	18 HP	
Diesel Tank Volume	2.64 gal (US)	
Displacement	52 in³	
Flywheel Output ISO	13 HP	
Battery	12 V, 20 Amp	
Туре	Water cooled model 3-cylinder diesel engine	
Make/Type	Yanmar 31NV70	
Emissions	Meets U.S. EPA Tier 4 Final/EU Stage V emission standards.	

Operating Weight	2061 lb
Operating Weight - Without Safety Frame	2061 lb
Operating Weight - With Safety Frame	2170 lb
Maximum Digging Depth	5.68 ft
Undercarriage Width - Extended	2.83 ft
Width	2.4 ft
Height - With ROPS Safety Frame Folded Down	4.94 ft
Maximum Dump Height	6.68 ft
Maximum Dozer Lift Height	8 in
Length - Undercarriage	4 ft
Maximum Vertical Dig Depth	4.43 ft
Minimum Front Linkage Swing Radius	3.77 ft
Boom Swing Angle - Left	55 °
Undercarriage Width - Retracted	2.33 ft
Boom Swing Angle - Right	56°
Maximum Reach	10.09 ft
Maximum Reach - Ground Level	9.92 ft
Transport Length - Arm Lowered	9 ft

Tail Swing Radius 2.41 ft Maximum Dozer Dig Depth 7 in Maximum Dig Height 9.39 ft Height - With ROPS Safety Frame Unfolded 7.47 ft Pumps 2 gear pumps Discharge Capacity 11.4+11.4 L/min (3+3 gal/min) Operating Pressure for the Work and Travel Hydraulics Operating Pressure Pivot Hydraulic Tank Capacity 3.7 gal (US) Gradeability 30°/58%
Maximum Dig Height 9.39 ft Height - With ROPS Safety Frame Unfolded 7.47 ft Pumps 2 gear pumps Discharge Capacity 11.4 + 11.4 L/min (3 + 3 gal/min) Operating Pressure for the Work and Travel Hydraulics 2466 psi Operating Pressure Pivot 1015 psi Hydraulic Tank Capacity 3.7 gal (US) Gradeability 30°/58%
Height - With ROPS Safety Frame Unfolded7.47 ftPumps2 gear pumpsDischarge Capacity11.4 + 11.4 L/min (3 + 3 gal/min)Operating Pressure for the Work and Travel Hydraulics2466 psiOperating Pressure Pivot1015 psiHydraulic Tank Capacity3.7 gal (US)Gradeability30°/58%
Pumps2 gear pumpsDischarge Capacity11.4 + 11.4 L/min (3 + 3 gal/min)Operating Pressure for the Work and Travel Hydraulics2466 psiOperating Pressure Pivot1015 psiHydraulic Tank Capacity3.7 gal (US)Gradeability30°/58%
Discharge Capacity Operating Pressure for the Work and Travel Hydraulics Operating Pressure Pivot Hydraulic Tank Capacity Gradeability 11.4 + 11.4 L/min (3 + 3 gal/min) 2466 psi 1015 psi 3.7 gal (US) 30°/58%
Operating Pressure for the Work and Travel Hydraulics Operating Pressure Pivot 1015 psi Hydraulic Tank Capacity 3.7 gal (US) Gradeability 30°/58%
Operating Pressure Pivot Hydraulic Tank Capacity 3.7 gal (US) Gradeability 30°/58%
Hydraulic Tank Capacity 3.7 gal (US) Gradeability 30°/58%
Gradeability 30°/58%
Travel Speed 1.12 mile/h
Track Width 7 in
Ground Clearance 5 in
Ground Pressure 3.5 psi
Machine Swing Speed 8 r/min
Number of Rollers - Each Side 2

Stick Length - Standard	34.8 in
Machine Overhang	12.5 in
Height	8 in
Dig Depth	7 in
Width	28 in
Lift Height	8 in
Sound Power Level (LWA) (to 2000/14/EG)	93 dB(A)

300.9D OPTIONAL EQUIPMENT

2 WAY (AUGER) AUXILIARY LINES TO THE STICK (NOT AVAILABLE IN ALL REGIONS)

BIO OIL

BUCKETS: 250 MM (10 IN); 350 MM (15 IN); 700 MM (2 FT 4 IN)

CUSTOM COLOR PAINT

FRONT GUARD

HAMMER

ROTATING BEACON